ctys-wakeup(1)

WoL and IPMI

$March\ 12,\ 2011$

Contents

1	NAME	2
2	SYNTAX	2
3	DESCRIPTION	2
4	OPTIONS	3
5	ARGUMENTS	3
6	EXIT-VALUES	4
7	SEE ALSO	5
8	AUTHOR	5
9	COPYRIGHT	5

2/5 ctys-wakeup(1)

.

1 NAME

ctys-wakeup - WoL and IPMI

2 SYNTAX

ctys-wakeup

```
[-d <level>]
[-h]
[-H <help-options>]
[-i <interface>]
[-n]
[-p <port>]
[-t <TCP/IP address>]
[-V]
[-X]
<mac-address>
```

3 DESCRIPTION

ctys-wakeup ctys-wakeup sends a so called MagicPacket(TM) to a given destination. In case a remote segment is addressed by setting the "-t" option, a UDP message is sent to port "9". The script consists of a few lines of bash code with a call to Netcat. So it could be adapted easily.

```
mac=$1;shift
ip=$1;shift
function buildWOLMagicPacket () {
 local _mac=$1;shift
 declare -a _pdu;
 function macAsc2Hex () {
   for i in ${@};do
    printf "\x$i"
   done
 }
 #frame
 _pdu=(ff ff ff ff ff);
 #MAC addr in "little endian"
 addr=(${mac: })
 addrLitteEndian=(${addr[0]} ${addr[1]} \
                  ${addr[2]} ${addr[3]} \
                  ${addr[4]} ${addr[5]});
 #add 16 duplications
 for((i=0;i<16;i++));do
   for m in ${addrLitteEndian[@]};do
     size=${#_pdu[@]}
```

ctys-wakeup(1) 3/5

```
_pdu[${size}]=$m
  done
done

macAsc2Hex ${_pdu[@]}
}

if [ -n "$ip" ];then
  printf "'buildWOLMagicPacket $mac'\n"|nc -u -w 1 $ip 9
  else
    buildWOLMagicPacket $mac
```

4 OPTIONS

- -d <level> Sets debug.
- -h Print help, refer to "-H" for additional information.
- -H <help-option> The extended help option is based on system interfaces for display of manpages, PDF and HTML documents. This comprises the man pages and installed manuals.

For additional help refer to the documents or type ctys -H help.

- -i
-i
-i interface The ethernet-broadcast interface for local segment. When used "-t" option is not applicable.
- -n No execution, evaluation only.
- -p <port> The port for destination, which is by default "9" for a hard-coded UDP message. It is not really relevant, might be used only for adaptation to firewall rule.
- -t <TCP/IP address> When provided the packet is send to destination. The destination address could be a "directed-broadcast" address, which has to be supported by the router.

E.g. OpenBSD requires "net.init.ip.directed-broadcast=1", and the appropriate pf-rules.

For 1.2.3.4:

Alternatively a "rdr" - Redirection could be set. When this option is not provided, a UDP packet will be sent to "255:255:255:255:9".

When used "-i" option is not applicable.

- -V Version.
- -X See ctys, terse for machine output.

5 ARGUMENTS

The MAC address of the targeted NIC, this could be evaluated by call of "ctys-macmap" and/or "ctys-vhost"

.

6 EXIT-VALUES

0: OK: Result is valid.

1: NOK: Erroneous parameters.

2: NOK: Missing an environment element like files or databases.

ctys-wakeup(1) 5/5

7 SEE ALSO

8 AUTHOR

Maintenance: <acue_sf1@users.sourceforge.net>

Homepage: http://www.UnifiedSessionsManager.org http://sourceforge.net/projects/ctys

Berlios.de: http://ctys.berlios.de http://www.i4p.com



9 COPYRIGHT

Copyright (C) 2008, 2009, 2010, 2011 Ingenieurbuero Arno-Can Uestuensoez For BASE package following licenses apply,

- for software see GPL3 for license conditions,
- for documents see GFDL-1.3 with invariant sections for license conditions,

This document is part of the DOC package,

• for documents and contents from DOC package see
'Creative-Common-Licence-3.0 - Attrib: Non-Commercial, Non-Deriv'
with optional extensions for license conditions.

For additional information refer to enclosed Releasenotes and License files.

